

Wi-PATH™ SX7T CDMA Premise Access Transport Hub

This feature-rich cellular device is the perfect solution for connectivity to communications networks



Features

- Dual band EVDO Rev A. 800/1900
- 1X RTT packet data
- RJ-11 interface with dialtone generation
- Group 3 analog fax
- Circuit switched data
- Superior voice quality

Also Featuring

- Easy installation
- 7 LEDs for signal strength, power, message alert and call status
- Connects multiple devices
- Access to the internet and e-mail

Ideal Applications

- Rapid deployment of wireless dialtone services
- Practical solution for business continuity or residential
- Remote site communications
- Industrial/Utility/Media/Transportation communications applications

Wi-PATH™ SX7T CDMA Premise Access Transport Hub

Unit Specifications

AC Power Adapter

110/230 VAC
Frequency: 50/60Hz
Plug Options:
US, UK, Euro

Rechargeable Battery Backup

Talk Time: > 1 Hours
Standby Time: > 8 Hours
Recharge time < 3 hours

Environment

Operating: 0C to 50C
Humidity: 5% to 95%
(non-condensing)

Dimensions (in inches)

W 7.5" x D 5.5" x H 1.8"

Transmit Power

800/1900: 250 mw

Connectors

USB Type A and B
RJ45
Dual RJ11
Barrel Type Power
TNC Antenna Connector

Antenna

High Performance
2dBi Antenna

Air Interface Standard

EVDO
1X RTT

Regulatory

FCC Part 15, 22, 24
CE
RoHS
CDMA - CTIA

Feature

- Quick and easy to install
- Flexible
- Improved antenna performance over mobile
- AC powered
- Small footprint
- Multiple standard connections

Benefit

- No wait for a service call (do it yourself)
- Instant voice, data and fax services
- More bars/less dropped calls/improved coverage
- No low battery
- Install anywhere on a desk or wall mount
- Plug in all office equipment, devices, peripherals

